

DISCO large-scale mowers ¹		9400 C DUO	9200 C AUTOSWATHER	1100 RC BUSINESS	1100 C BUSINESS	9200 C BUSINESS	9200 BUSINESS	9200 RC CONTOUR	9200 C CONTOUR	9200 CONTOUR	8500 RC CONTOUR	8500 C CONTOUR	8500 CONTOUR	1100 TREND	9200 TREND	8500 TREND
Dimensions and weights																
Working width ²	m	9.10 / 8.90	9.10 / 8.90	9.60-10.70 ³	9.40-10.70 ³	9.10 / 8.90	9.10 / 8.90	9.10 / 8.90	9.10 / 8.90	9.10 / 8.90	8.30 / 8.10	8.30 / 8.10	8.30 / 8.10	9.60-10.70 ³	9.10 / 8.90	8.30 / 8.10
Hitch category		III	III	III	III	III	III (II)	III	III	III (II)	III	III	III (II)	III	III (II)	III (II)
PTO shaft speed	rpm	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)
Transport width	m	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95
Machine height	m	3.81	3.89	3.79	3.79	3.89	3.89	3.89	3.89	3.89	3.64	3.64	3.64	3.79	3.64	3.64
Weight	approx. kg	2800	3590 (+ 40 ⁴)	3570	3520	2360	2010	2600	2320	1980	2300	2100	1830	2600	1940	1790
Mower																
MAX CUT mower bar ⁵		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
ACTIVE FLOAT suspension		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Discs (2 knives per disc)		2 x 8	2 x 8	2 x 9	2 x 9	2 x 8	2 x 8	2 x 8	2 x 8	2 x 8	2 x 7	2 x 7	2 x 7	2 x 9	2 x 8	2 x 7
Quick blade change		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Conditioner																
Conditioner speed	rpm	910	1100 / 990	940	910	910	–	940	910	–	940	910	–	–	–	–
Hydraulics																
Hydraulic spool valves		LS (or 1 x sa + free return) + 1 x sa for P2						1 x sa + 1 x da						2 x da (+ 1 x sa)	2 x sa (+ 1 x sa ⁶)	
Operation																
ISOBUS-compatible		●	●	●	●	●	●	● (pre-selection)	● (pre-selection)	● (pre-selection)	● (pre-selection)	● (pre-selection)	● (pre-selection)	–	–	–
EASY on board		○	○	○	○	○	○	–	–	–	–	–	–	–	–	–
COMMUNICATOR II		○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	–	–	–	–	–	–	–	–	–
OPERATOR		–	–	–	–	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	–	–	–
ISOBUS cable		○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	–	–	–
Hectare count for OPERATOR		–	–	–	–	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	–	–	–
Order printer		○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	○ ⁷	–	–	–
Optional																
Hydraulically foldable protective side covers		●	○	●	●	●	●	○	○	○	–	–	–	●	–	–
Wide crop spreader		○	●	–	○	○	–	–	○	–	–	○	–	–	–	–
Adjustable swathing plates		●	●	●	●	●	–	●	●	–	●	●	–	–	–	–
Outside swathing disc		–	–	–	–	–	●	–	–	●	–	–	●	○	○	○
High-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Twin high-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Wear skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Bar protection device (for intensive use conditions)		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Warning signs with lighting		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Hydraulic transport locking device		●	●	●	●	●	●	●	●	●	●	●	●	●	–	–
Breakback protection		–	–	–	–	–	–	●	●	●	●	●	●	–	●	●
Mechanical		–	–	–	–	–	–	●	●	●	●	●	●	–	●	●
Hydraulic		●	●	●	●	●	●	–	–	–	–	–	–	●	–	–

¹ C = tine conditioner, RC = roller conditioner, no suffix = without conditioner

² Working width including front mower 3600 FRC / FC / F PROFIL, 3200 FRC / FC / F PROFIL, 3150 F

³ According to front mower used, infinitely variable adjustment

⁴ Central lubrication

⁵ Standard cut height 40 mm (infinitely variable adjustment 30–70 mm)

⁶ For individual lifting function

⁷ Option

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.